

## Model 2284



**150W  
continuous  
300W peak**

- "E" marked to vehicle directive (95/54/EC)
- 12V, and 24VDC input types
- 230V AC RMS +5/-10% 50Hz. output
- Low input alarm
- High input alarm
- Short circuit proof
- Overvoltage protected
- Overtemperature protection
- Size: 217 x 148 x 67 mm




- "E" marked to vehicle directive (95/54/EC)
- 12V, and 24VDC input types
- 230V AC RMS +5/-10% 50Hz. output
- Low input alarm
- High input alarm

## Model 2285



**300W  
continuous  
500W peak**

- Short circuit proof
- Overload protected
- Overtemperature protection
- Size: 217 x 148 x 67 mm



**600W  
continuous  
1000W peak**

## Model 2286

- "E" marked to vehicle directive (95/54/EC)
- 12V, and 24VDC input types
- 230V AC RMS +5/-10% 50Hz. output
- Short circuit proof
- Low input alarm
- Short circuit proof
- Overvoltage protected
- Overtemperature protection
- Size: 335 x 238 x 83 mm



- "E" marked to vehicle directive (95/54/EC)
- 12V, and 24VDC input types
- 230V AC RMS +5/-10% 50Hz. output
- Low input alarm
- High input alarm

## Model 2287



**1000W  
continuous  
2000W peak**

- Short circuit proof
- Overload protected
- Overtemperature protection
- Size: 395 x 238 x 83 mm

