

Dimensions

A CASE
WT. 0.9Kg

DC OUTPUT
AC INPUT
OVP (OPT)

.188 DIA. MTG. HOLES (8PL)

INCH	mm	
A	4.00	101.60
B	3.375	85.73
C	4.87	123.70
D	4.125	104.78
E	0.50	12.70
F	1.62	41.15
G	0.75	19.05
H	0.450	11.43
J	0.38	9.65
K	0.57	14.48
L	2.80	68.04
M	0.794	20.17

FUSE AT: 0.5/0.25 AMPS FOR 100-120/220-240 VAC

AAA CASE
WT. 2.3 Kg

DC OUTPUT
AC INPUT
OVP (OPT)

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	10.25	260.35
B	9.250	234.95
C	0.650	16.270
D	4.00	101.60
E	3.375	85.73
F	0.37	9.40
G	1.250	31.75
H	0.75	19.05
J	0.450	11.43
K	2.50	63.50

FUSE AT: 1.0/0.5 AMPS FOR 100-120/220-240 VAC

AA CASE
WT. 0.9 Kg

DC OUTPUT
OVP (OPT)
AC INPUT

.188 DIA. MTG. HOLES (8 PL)

INCH	mm	
A	4.00	101.60
B	3.375	85.73
C	6.50	165.10
D	5.750	146.05
E	0.75	19.05
F	0.450	11.43
G	1.62	41.15
H	0.25	6.35
J	0.50	12.70
K	0.955	24.26
L	2.37	60.20
M	0.57	14.48

FUSE AT: 0.5/0.25 AMPS FOR 100-120/220-240 VAC

B CASE
WT. 1.8 Kg

DC OUTPUT
OVP (OPT)
AC INPUT

.188 DIA. MTG. HOLES (12PL)

INCH	mm	
A	4.87	123.70
B	4.125	104.78
C	0.25	6.35
D	5.62	142.75
E	4.875	123.83
F	0.50	12.70
G	2.50	63.50
H	1.250	31.75
I	0.75	19.05
K	0.450	11.43
L	2.85	72.39
M	1.025	26.04
N	0.665	16.89

FUSE AT: 1.0/0.5 AMPS FOR 100-120/220-240 VAC

BB CASE
WT. 1.8 Kg

DC OUTPUT
OVP (OPT)
AC INPUT

.188 DIA. MTG. HOLES (12PL)

INCH	mm	
A	4.87	123.70
B	4.125	104.78
C	0.25	6.35
D	7.00	177.80
E	6.250	158.75
F	0.50	12.70
G	1.250	31.75
H	2.50	63.50
I	0.75	19.05
K	0.450	11.43
L	0.665	16.89
M	1.025	26.04
N	2.85	72.39

FUSE AT: 1.0/0.5 AMPS FOR 100-120/220-240 VAC

BBB CASE
WT. 3.6 Kg

DC OUTPUT
OVP (OPT)
AC INPUT

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	11.00	279.40
B	7.900	199.50
C	3.00	76.20
D	4.87	123.70
E	4.125	104.78
F	0.50	12.70
G	1.260	31.75
H	0.75	19.05
J	0.450	11.43
K	2.75	69.85

FUSE AT: 2.0/1.0 AMPS FOR 100-120/220-240 VAC

C CASE
WT. 2.7 Kg

AC INPUT
DC OUTPUT
OVP (OPT)

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	7.00	177.80
B	6.250	158.75
C	4.87	123.70
D	4.125	104.78
E	0.50	12.70
F	1.250	31.75
G	0.75	19.05
H	0.450	11.43
J	2.75	69.85
K	0.38	9.65
L	0.640	16.26
M	3.35	85.09
N	1.00	25.40

FUSE AT: 2.0/1.0 AMPS FOR 100-120/220-240 VAC

CC CASE
WT. 3.2 Kg

AC INPUT
OVP (OPT)
DC OUTPUT

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	9.38	238.25
B	8.375	212.73
C	0.50	12.70
D	4.87	123.70
E	4.125	104.78
F	1.250	31.75
G	2.75	69.85
H	0.75	19.05
J	0.450	11.43

FUSE AT: 2.0/1.0 AMPS FOR 100-120/220-240 VAC
HCC512: 3.0/1.5 AMPS FOR 100-120/220-240 VAC

D CASE
WT. 3.4 Kg

AC INPUT
OVP (OPT)
DC OUTPUT

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	9.00	228.60
B	8.000	203.20
C	0.50	12.70
D	4.87	123.70
E	4.125	104.78
F	1.250	31.75
G	2.75	69.85
H	0.75	19.05
J	0.450	11.43

FUSE AT: 2.0/1.0 AMPS FOR 100-120/220-240 VAC

DBB CASE
WT. 5.0 Kg

DC OUTPUT
OVP (OPT)
DC OUTPUT
AC INPUT

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	14.25	361.95
B	12.750	323.25
C	5.00	127.00
D	4.87	123.70
E	4.125	104.78
F	0.50	12.70
G	1.250	31.75
H	0.75	19.05
I	2.75	69.85
J	0.450	11.43
K	0.625	15.88

FUSE AT: 3.0/1.5 AMPS FOR 100-120/220-240 VAC

E CASE
WT. 4.5 Kg

AC INPUT
OVP (OPT)
DC OUTPUT

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	14.00	355.60
B	13.000	330.20
C	4.87	123.70
D	4.125	104.78
E	0.50	12.70
F	1.250	31.75
G	0.75	19.05
H	0.650	16.51
J	2.75	69.85

FUSE AT: 3.0/1.5 AMPS FOR 100-120/220-240 VAC

131 CASE
WT. 4.0 Kg

DC OUTPUT
AC INPUT
OVP (OPT)

.188 DIA. MTG. HOLES (16PL)

INCH	mm	
A	11.00	279.40
B	7.000	177.80
C	0.50	12.70
D	0.25	6.35
E	4.87	123.70
F	4.125	104.78
G	1.250	31.75
H	0.75	19.05
J	0.450	11.43
K	2.75	69.85
L	0.600	15.24
M	0.640	16.26
N	3.35	85.09

FUSE AT: 3.0/1.5 AMPS FOR 100-120/220-240 VAC